

TECHNICAL DATA SHEET

(Antistatic MFQ-AS1001)

- Product Description:**

MFQ-AS1001 is an antistatic masterbatch that have good performance due to good balance of incompatibility between base resin and additive.

MFQ-AS1001 is recommended for increasing conductivity (dissipates charge) and decrease resistance and charge decay time.

MFQ-AS1001 prevents dust pick up, spark and blocking plastic layers.

MFQ-AS1001 improves de-molding of plastic product and makes more uniformity in plastic foam.

MFQ-AS1001 contains special anti-oxidants to help processing and final product protection.

- General Properties:**

Forms •Granule/Pellets

Color •Natural

- Technical Specifications:**

Carrier Resin	PE		
Active Ingredients	≈ 10 % Stearate derivative		
Thermal Stabilizer	Yes		
MFI	≈ 1.2	gr/10min.	(@ 230 °C ,2.16 kg)
Specific Density	≈ 0.91	gr/cm ³	

ATTENTION

- ✓ **Dosage:** 1 % to 3 % film depending on final application and thickness.
- ✓ **Lifetime and Storage:** Not to exceed 10 months. Keep in cool and dry place under shelter for long periods.

* This product packed in PP Woven bag of 25 kg each

Address No.: 811, Eighth Floor, Palmyra Commercial and Administrative Complex, Madani Avenue, Western Janbazan, Narmak, TEHRAN – IRAN www.marinafq.com

TEL: +98-21-77850569

+98-21-77850591

+98-21-77850536

WhatsApp: +98-9916593655

Email: commercial@marinafq.com

www.marinafq.com