

## TECHNICAL DATA SHEET

### (Additive MFQ-STAB-1031)

- **Product Description:**

MFQ-STAB-1031 excellent long-term heat stability  
MFQ-STAB-1031 pigmenting effect of basic primary lead Stabilizers beneficial in light colored applications  
MFQ-STAB-1031 low solubility in water, no leaking into the environment  
MFQ-STAB-1031 no odor during processing and in the final product  
MFQ-STAB-1031 No detrimental effects on the softening temperature of rigid PVC

- **General Properties:**

Forms	•Flake
Color	•Dark

- **Technical Specifications:**

Compounds	organic and inorganic materials
Solubility in water	Indissoluble
Ash	1±23
Moisture Content	max 1 %
Phr	5/2-5/3
Soft Point(°C) orMP	1±100 °C

**ATTENTION**

- ✓ **Dosage:** 5% to 10% film depending on final application and thickness.
- ✓ **Lifetime and Storage:** Not to exceed 12-18 months. Keep in cool and dry place under shelter for long periods.

\* This product packed in PP Woven bag of 25 kg each

Address No.: 811, Eighth Floor, Palmyra Commercial and Administrative Complex, Madani Avenue, Western Janbazan, Narmak, TEHRAN – IRAN [www.marinafq.com](http://www.marinafq.com)

TEL: +98-21-77850569

+98-21-77850591

+98-21-77850536

WhatsApp: +98-9916593655

Email: [commercial@marinafq.com](mailto:commercial@marinafq.com)

[www.marinafq.com](http://www.marinafq.com)